

See price list for available finishes (finish chart is on the order form)



Werner T6200 Series Twin StepLadders

- Orange electrically non-conductive side rails.
- Tool-Tra-Top® - with drill holster, tool and paint can holders, and small parts tray.
- 4 rivets attach top to each front rail .
- Top steps are knee-braced.
- Double riveted, slip-resistant Traction-Tred® steps
- Heavy duty internal spreaders .
- EDGE®* - molded brace and foot pad combination provides enhanced bracing strength and increased protection against damage .
- Energy Diffusing Geometry.
- Every rivet backed up by metal part or washer to protect rails.

Note: Designed for one or two person jobs. When used as a double stepladder, the maximum load per side, including person and materials, shall not exceed the duty rating of ladder.

Dimensions

- Top: 8-1/2" x 13" .
- Steps: 3" wide.
- Front Rails: 3-1/8" wide.
- Flange: 1-3/16" wide.

Models	Size	Approx. Width	Approx. Spread	Approx. Cu. Ft. Per Unit
076-T6303	3'	18-1/8"	29"	3.1
076-T6204	4'	19-7/8"	36-1/8"	4.6
076-T6205	5'	21-5/8"	43-1/8"	6.2
076-T6206	6'	23-3/8"	50-1/8"	8.0
076-T6208	8'	26-7/8"	64-1/8"	12.3
076-T6210	10'	30-3/8"	78-1/8"	17.3
076-T6212	12'	33-7/8"	92-1/8"	23.2



Werner 6200 Series StepLadders

- Orange, electrically non-conductive side rails .
- Tool-Tray Top® - with drill holster and convenient tray for tools.
- 4 rivets attach top to each front rail.
- Shoulder bolt and nut on top hinge.
- Back-up plates reinforce all top connectors.
- Handy paint can hanger on back side of top.
- Top steps and rear horizontals are knee-braced.
- Double riveted, slip-resistant Traction-Tred® steps.
- Heavy duty internal spreaders.
- Full set of rear horizontals spaced one per foot.
- EDGE - molded brace and foot pad combination provides enhanced bracing strength and increased protection against damage.
- Energy Diffusing Geometry.
- Every rivet backed up by metal part or washer to protect rails.
- Optional yellow molded pail shelf kit, model no. 76-2.

Dimensions:

- Top: 5-3/4" x 13".
- Front Rails: 3-1/8" wide.
- Flange: 1-3/16" wide.
- Steps: 3" wide.
- Rear Rails: 1-7/8" wide.
- Flange: 1-3/16" wide.

Models	Size	Approx. Width	Approx. Spread	Approx. Cu. Ft. Per Unit
076-6203	3'	18-1/8"	23-1/8"	2.0
076-6204	4'	19-7/8"	29"	3.0
076-6205	5'	21-5/8"	35-1/8"	4.1
076-6206	6'	23-3/8"	41-1/4"	5.3
076-6207	7'	25-1/8"	47-1/2"	6.6
076-6208	8'	26-7/8"	53-5/8"	8.1
076-6210	10'	30-3/8"	65-7/8"	12.5
076-6212	12'	33-7/8"	78-1/4"	15.0

See price list for available finishes (finish chart is on the order form)



Werner 7400 Series StepLadders

- Orange, electrically non-conductive side rails.
- NEW heavy gauge Tool-Tray Top®.
- Thick side plates.
- Shoulder bolt and lock nut on top hinge; 4 solid aluminum rivets attach top to each front rail.
- Back-up aluminum plates reinforce all top connectors.
- Slip resistant Traction-Tred® steps are double riveted and knee-braced.
- Extra heavy duty internal spreaders.
- Full set of rear horizontals are knee braced and spaced one per foot .
- NEW Glas* Mark® violator stripes on rails allow ladder to be more visible.
- NEW! The EDGE®* bracing system helps to decrease damage to rail.
- NEW aluminum external rail shield helps protect against abrasion damage.

Dimensions

- Top: 7-1/4" x 14-7/8".
- Front Rails: 3-1/8" wide.
- Flange: 1-3/16" wide.
- Steps: 3" wide.
- Rear Rails: 1-7/8" wide.
- Flange: 1-3/16" wide.

Models	Size	Approx. Width	Approx. Spread	Approx. Cu. Ft.	Approx. Shipping Wt. Lbs.
076-7403	3'	19-3/4"	24-3/8"	2.5	13.5
076-7404	4'	21-1/2"	30-1/2"	3.5	16.5
076-7405	5'	23-1/4"	36-3/4"	4.6	20.0
076-7406	6'	25"	42-7/8"	5.8	23.5
076-7407	7'	26-3/4"	49"	7.1	28.0
076-7408	8'	28-1/2"	55-1/4"	8.5	32.0
076-7410	10'	32"	67-1/2"	11.4	40.0
076-7412	12'	35-1/2"	79-7/8"	14.8	49.5



Werner 7300 Series StepLadders

- Yellow, electrically non-conductive side rails .
- NEW heavy gauge Tool-Tra-Top® offers strength, durability and utility.
- Slip-resistant Traction-Tred® steps are single riveted and knee-braced.
- Heavy duty internal spreaders
- Glas*Mark® violator stripes on rails allow ladder to be more visible.
- The EDGE®* bracing system helps to decrease damage to rail.
- Full set of rear horizontals spaced one foot apart
- Every rivet backed up by metal parts or washers to protect rails.
- Thick side plates
- Shoulder Bolt & Lock nut on top hinge; 4 solid aluminum rivets attach top to each front rail.

Dimensions

- Top: 7-7/8" x 14".
- Front Rails: 3-1/8" wide.
- Flange: 1-3/16" wide.
- Rear Rails: 1-7/8" wide.
- Flange: 1-3/16" wide.
- Steps: 3" wide.

Models	Size	Approx. Width	Approx. Spread	Approx. Cu.Ft. Per Unit
076-7303	3'	19-3/4"	23-1/2"	2.5
076-7304	4'	21-1/2"	29-3/4"	3.5
076-7305	5'	23-1/4"	35-7/8"	4.6
076-7306	6'	25"	42"	5.8
076-7308	8'	28-1/2"	54-3/4"	8.5
076-7310	10'	32"	66-5/8"	11.4
076-7312	12'	35-1/2"	79"	14.8

Ladders Locker Hardware

See price list for available finishes (finish chart is on the order form)




Werner Step Stools

- Orange electrically non-conductive side rails.
- Heavy duty broad steps and top. Deep treads provide slip resistance.
- Locking spreader permanently stays open, very durable & stable.
- Extra large feet for use on gratings.

Dimensions

- Top: 9" x 14".
- Front Rails: 6" wide.
- Front Flange: 1-1/8" wide.
- Steps: 6".
- Rear Rails: 1-7/8" wide.
- Rear Flange: 1-3/16" wide.

Models	Size	Max. Standing Height	Approx. Width	Approx. Spread	Approx. Cu. Ft. Per Unit
076-SSF02	2'	20"	17"	21"	2.6
076-SSF03	3'	30"	8-3/4"	27-1/2"	4.0



National Cabinet Disc Tumbler Locking Handles

- Application-RH or LH doors of metal lockers and cabinets. Choice of spindle lengths and mounting. Spindles accept both C8756 latch plate and C8757 tongue. Spindles can be cut to fit special requirements.
- Operation -Key removable in both locked and unlocked positions.
- Keying - Keys together all other disc tumbler locks using D8785 KB
- Packaging - Included two keys and mounting brackets

Models	Type of Mount	Spindle Length
048-8747 26D KA C415A	Rear	1.5" CTC*
048-8751 26D KD	Rear	1"
048-8754 26D KA C415A	Rear	3"
048-8754 26D KD	Rear	3"
048-8758 26D KD	Front	1"
048-8759 26D KD C415A	Front	3"

*5/16" square spindle w/8-32 tapped end hole



National Cabinet Latch Plate & Tongue

Models	Description
048-C8756 2C	3 point latch plate w/tongue. Used with locking bars.
048-C8757 2C	Single point latch tongue