


See price list for available finishes (finish chart is on the order form)

Slide Bolts


- **Shelf Pack:**
10 Polybagged
- **Finishes:** 605, 613, 609, 619, 620, 625, 626
- **Material:** Solid Brass
- Furnished with Rim and Mortise strikes



Models	Dimensions	ANSI
022-SB-2	2"	L04151
022-SB-3	3"	L04151
022-SB-4	4"	L04151
022-SB-6	6"	L04151
022-SB-12	12"	L04151

Slide Bolts

- **Shelf Pack:** 10 Polybagged
- **Finishes:** 626, 630
- **Material:** Stainless Steel
- All stainless steel components
- Top and bottom strikes available
- Padlock not included



Model	Dimensions	Throw
022-1582	8"	1"

DCI

Surface Door Bolts

- Surface door bolts are of heavy steel construction with a throw of 1 3/16", insuring maximum strength and security on both inswinging and outswinging metal or wood doors. All bolts are available with choice of three strikes. Mortise and L-shape strike furnished standard; rim strike No. 3 optional.
- Specify UL Listed 1008F and 1012F for fire doors, and 1008P and 1012P for security bolt with padlock bracket.



Models	Description
019-1008	8" Bolt
019-1012	12" Bolt
019-1008F	8" Bolt For Fire Doors
019-1012F	12" Bolt For Fire Doors
019-1008P	8" Bolt w/padlock bracket
019-1012P	12" Bolt w/padlock bracket

Iico

Mortise Bolts



037-5050

- Satin brass.
- 5/8" throw.
- Turn knob one side only.
- Fits doors 1-1/4" to 1-7/8" thick 2" B.S.

Model

037-5050 04 51




037-5051

- 5/8" throw.
- Operates by key outside.
- Fits doors 1" to 1-1/2" thick.

Model

037-5051 04 51



038-S48B3

Ives

Mortise Bolts

- Steel bolt.
- 1/2" throw.
- Brass finish.

Model

038-S48B3

See price list for available finishes (finish chart is on the order form)

Ives

1600 Series Surface Bolts

- 1" Throw.
- Fully concealed mounting prevents vandalism.
- Units furnished with either universal top strike or flat bottom strike.
- Units packed with wood and machine screws to meet most field conditions.
- Sex bolts available where required.
- Body: 8" Long x 7/8" Wide x 3/4" Thick.
- Overall Knob or Lock Housing Projection: 1-1/2".
- Top Strike: 1-1/4" Wide x 7/8" Tall x 15/16" Deep.
- Bottom Strike: 3" Long x 1" Wide x 1/8" Thick.



Models	Description
038-SB1630T	8" Steel, Universal Top Strike
038-SB1630B	8" Steel, Flat Bottom Strike
038-SB1640T	8" Brass, Universal Top Strike
038-SB1640B	8" Brass, Flat Bottom Strike

Ives

Surface Bolts

- Surface bolt has 1-1/4" throw for maximum security.
- Ideal for all types of doors.
- Unit locks in both the up and down position.
- Accepts padlock (not furnished) with maximum 3/8" diameter shackle, minimum 1-3/4" shackle opening height.
- Units packed with one-way screws for added security. Standard screws also supplied.
- Constructed of heavy duty steel.
- Meets ANSI/BHMA A 156.16.
- Optional Sex Bolts and Mortise Strike available.
- Bar: 3/4" Wide x 3/4" Thick.
- Overall Width: 2-1/32".
- Overall Projection: 2-1/16".
- Top Strike: 1-1/2" x 1-1/2" Angle, 3/16" Thick.
- Optional Mortise Strike: 3-1/2" Long x 1-5/8" Wide x 1/8" Thick.




Models	Description
038-SB360 T12	12" Universal Top Strike
038-SB360 B12	12" Flat Bottom Strike
038-SB360 T24	24" Universal Top Strike
038-SB360 B24	24" Flat Bottom Strike

Ives

Surface Bolts

- Surface bolt has 1-3/16" throw for maximum security.
- Strong tension springs prevent creep.
- Ideal for all types of doors.
- Units packed with standard screws for added security.
- Constructed of heavy duty steel.
- Meets ANSI/BHMA A156.16 L84161
- Optional sex bolts and thru bolts available.
- Bar: 3/4" Wide x 1/4" Thick
- Overall Width: 2-1/32"
- Overall Projection: 1-5/16"
- Top Strike: 1-1/2" x 1-1/2" Angle, 3/16" Thick
- Bottom Strike: 3-1/2" Long x 1-5/8" Wide x 1/8" Thick



Models	Description
038-SB453 8	8" Top and Bottom Strike
038-SB453 12	12" Top and Bottom Strike
038-SB453 18	18" Top and Bottom Strike
038-SB453 24	24" Top and Bottom Strike

Ives

Surface Bolts

- Surface bolt has 1-3/16" throw for maximum security.
- Ideal for all types of doors.
- Constructed of heavy duty steel.
- Bolts are UL listed up to 3 hours when used on the inactive door of a pair up to 10' in height.
- Meets ANSI/BHMA A156.16 L84161
- Finishes: US2C, US10, US10B, US26D.
- Optional sex bolts and thru bolts available.
- Bar: 3/4" Wide x 1/4" Thick
- Overall Width: 2-1/32"
- Overall Projection: 1-5/16"
- Top Strike: 1-1/2" x 1 1/2" Angle, 3/16" Thick
- Bottom Strike: 3-1/2" Long x 1-5/8" Wide x 1/8" Thick



Models	Description
038-454 5	5" Top Strike
038-454 8	8" Top & Bottom Strike
038-454 12	12" Top & Bottom Strike
038-0454	10" Top & Bottom Strike