

See price list for available finishes (finish chart is on the order form)



**ABH**  
**9000 Series Heavy Duty Overhead Door Holders/Stops Surface Mounted**

- Specify door size, finish, function and if door is hung on butt, offset or center hung pivots. Available in hold open, stop or friction.
- For single acting doors.
- Non-handed/reversible.
- Hold-open knob can be disengaged to act as a stop only.
- Minimum door opening 30".
- Finishes available 652 & US32D.

<b>Model</b>
<b>001-9000</b>



**ABH**  
**4400 Series Medium Duty Door Holders/Stop Surface Mounted**

- Specify door size, finish, function and if door is hung on butt, offset or center hung pivots. Available in hold open, stop or friction.
- For single acting doors.
- Non-handed/reversible.
- Automatic hold-open and release by push and pull on door.
- Hold-open can be disengaged to act as stop only.
- Maximum swing 110° minimum door opening 24".
- Finishes available 652 & US32D.

<b>Model</b>
<b>001-4400</b>



**ABH**  
**7000 Series Surface Mounted Overhead Door Holder/Stop**

- For exterior, vestibule, and interior single acting doors.
- Maximum door opening 110 degrees, minimum door thickness 1-1/4".
- Wood, machine screws and grommet nuts included.

Door Opening		Holder Number	
Butts Offset Pivots	Center Hung	Hold Open	Stop
23" 28 15/16"	24" 31 15/16"	001-7010	001-7020
29" 34 15/16"	32" 38 7/16"	001-7011	001-7021
35" 40 15/16"	38 1/2" 44-3/16"	001-7012	001-7022
41" 46 15/16"	44 1/4 " 50 3/16"	001-7013	001-7023
47"+Greater	50 1/4" 60"	001-7014	001-7024
BHMA Number		001-C08511	001-C08541
Fed. Spec. Type		001-GJ70	



**Glynn-Johnson**  
**Overhead Door Holders**

Models	Description
<b>031-900S</b>	Stop Only
<b>031-900H</b>	Hold Open
<b>031-454S</b>	Stop Only
<b>031-414S</b>	Hold Open

See price list for available finishes (finish chart is on the order form)



## Ives Hold Open Arms

- The 70/79 Series surface-mounted holders and stops combine rugged construction and simple installation, for extremely reliable heavy-duty door control.
- The 70 Series is designed around a 1/2" (12.7 mm) diameter 300 Series stainless steel bar, while the 79 Series utilizes a 3/4" (19.1 mm) diameter bar, also constructed of 300 Series stainless steel.
- Components including jamb brackets, door brackets and hold-open/shock absorber mechanisms are constructed primarily of brass and stainless steel. Several components are fabricated of corrosion-resistant steel material.
- Models are available in hold-open and stop-only functions, each offered in five sizes.

Models	Description
031-700H	Hold-Open: Heavy-Duty
031-700S	Stop-Only: Heavy-Duty
031-790H	Hold-Open: Extra Heavy-Duty
031-790S	Stop-Only: Extra Heavy-Duty

Classified by UL/cUL as miscellaneous Fire Door Accessory. Applies to surface overhead stops used in hollow metal and wood fire doors.

## Ives Floor & Wall Stops/Holders

	038-WS407-CVX	Wrought Wall Bumpers
	038-WS402-CVX	Wrought Wall Bumpers
	038-WS407-CCV	Wrought Wall Bumpers
	038-WS402-CCV	Wrought Wall Bumpers
	038-WS447	Wall Bumper
	038-FS444	Floor Type Bumper
	038-FS446	Manual Floor Type Holder
	038-FS442	Floor Type Bumper

## Ives Kick Down Door Holders

- Economical, durable cast iron.
- For doors with door-to-door clearance up to 2".
- BHMA L11381, ANSI 156.16.
- Replaceable non-marring, corrugated rubber shoes.



Models	Description
038-FS544-4	Bronze
038-FS544-5	Brass

See price list for available finishes (finish chart is on the order form)



019-3330X



019-3360X



019-3340X

## DCI Floor Stops

Models	Bumper Contact Height	ANSI/BHMA	Finish
019-3330X	1 5/8"	ANSI/BHMA Standards 156.16, L12131	Heavy Duty Cast Bronze or Brass
019-3340X	2 1/4"	ANSI/BHMA Standards 156.16, L12131	Heavy Duty Cast Bronze or Brass
019-3360X	2 5/8"	ANSI/BHMA Standards 156.16, L12131	Heavy Duty Cast Bronze or Brass

## DCI Floor Stops/holders

Floor stops and holders are manufactured of solid cast brass or bronze. Specify for commercial applications where strength and durability are required. Universal mounting package supplied for all types of applications. Available in architectural finishes.

### 019-3347X

- 2 1/4" Bumper Contact
- Conforms to ANSI/BHMA Standards 156.16, L11371



### 019-3367X

- 2 5/8" Bumper Contact
- Conforms to ANSI/BHMA Standards 156.16, L11371



Model	Description
019-3347X	2-1/4" Contact
019-3367X	2-5/8" Contact

## DCI Wall Stops/ Holders



019-3260X



019-3267X

- Conforms to ANSI/BHMA A156.16, L12021 Standards. Heavy duty with a 3 7/8" projection is manufactured of solid cast brass or bronze, and is available in architectural finishes.
- Wall stop with hook and holder conforms to ANSI/BHMA A156.16, L11351 Standards. Heavy duty with a 3 3/4" projection is manufactured of solid cast brass or bronze, and is available in architectural finishes.

Models	Description
019-3260X	3-7/8" Projection
019-3267X	3-3/4" Projection

## DCI Dome Stops



019-3310X



019-3320X

- The 3310X low profile dome stop conforms to ANSI/BHMA 156.16, L12141, and the 3320X high profile dome stop conforms to ANSI/BHMA 156.16, L12161. Manufactured of solid cast brass or bronze with a durable rubber cushion. Plated cast risers are available for carpet and threshold installations. Universal mounting package supplied for all types of applications. Available in architectural finishes.

Models	Description
019-3310X	Low Profile 1" High
019-3320X	High Profile 1-1/4" High



019-3104/  
019-3105



019-3114/  
019-3115

## DCI Kick Down Door Holders

The spring hinge allows the holder to stay in the flipped up position when door is closed, and the serrated rubber shoe firmly holds the door in an open position. Replacement shoes are available in threaded or screw type.

Models	Descriptions
019-3104	4" rails, cast iron ANSI/BHMA 156.16 L71381
019-3105	5" rails, cast iron ANSI/BHMA 156.16 L71391
019-3114	4" rails, brass/bronze ANSI/BHMA 156.16 L11381
019-3115	5" rails, brass/bronze ANSI/BHMA 156.16 L11391










See price list for available finishes (finish chart is on the order form)














## Commercial Stoppers and Bumpers

- All finished In 626 for your commercial business
- Assortment Includes 2 each of The following:  
 1406 1407 1440 1455 1468\* 1471  
 1444 1446 1448 1473 1477  
 \*Finish not applicable

<b>Model</b>
<b>022-CP01</b>

## Individual Door Stops and Bumpers

Models	Description	
<b>022-1406 626</b>	Convex Wall Bumper 2-1/2 Diameter Plastic Anchor & Plastic Dry Wall Anchor	
<b>022-1407 626</b>	Concave Wall Bumper 2-1/2 Diameter Plastic Anchor & Plastic Dry Wall Anchor	
<b>022-1401 626</b>	Wall Bumper 1-13/16" Diameter	
<b>022-1402 626</b>	Wall Bumper 1-1/2" Diameter	
<b>022-1410 626</b>	Wall Bumper 3-7/8" Diameter	
<b>022-1440 626</b>	Low Style Floor Stop 1/4" x 1-5/8" Base W/S & MS & Exp. Shield Cast Brass	
<b>022-1442 626</b>	Low Style Floor Stop 1/4" x 1-5/8" Base W/S & MS & Exp. Shield Cast Brass	
<b>022-1443 626</b>	Floor Stop 1" x 3/16"	
<b>022-1444 626</b>	Floor Stop 1" x 1/2"	

<b>022-1445 626</b>	3/4" High x 1-5/8" Diameter Base 1440 and 1446 combo pack	
<b>022-1446</b>	Riser Floor Stop	
<b>022-1449 626</b>	Door Stop 2-1/2" projection 2-1/4" x 1-5/8"	
<b>022-1448 626</b>	Door Stop 1-5/8" projection 2-1/4" x 1-5/8"	
<b>022-1455 626</b>	Door Holder Cast Aluminum 4"	
<b>022-1465 626</b>	Door Holder Solid Brass 4"	
<b>022-1467 626</b>	Door Holder Solid Brass 5"	
<b>022-1466 626</b>	Door Holder Cast Iron 4"	
<b>022-1468</b>	Replacement Tip	
<b>022-1471 626</b>	Door Stop 2-1/4" projection	
<b>022-1473 626</b>	Door Stop 2-1/4" projection	
<b>022-1475 626</b>	Door Stop 2-1/4" x 3-1/2"	
<b>022-1477 626</b>	Door Stop 2-1/4" x 3-1/2"	

See price list for available finishes (finish chart is on the order form)

## Ives Floor Stops

- Designed to blend with all types of construction.
- Accommodates door undercut up to 1-1/2".
- Heavy Duty cast brass or aluminum construction.
- Non-marring rubber bumper.
- Place with expansion shield & tamper.
- Meets ANSI/BHMA 156.16, L12131 for brass. L32121 for aluminum.
- WS - Packed with wood screws



Models	Overall Height	Overall Length	Base Depth
038-FS441	2-1/8"	2-7/8"	1-5/8"
038-FS441-WS	2-1/8"	2-7/8"	1-5/8"
038-FS442	2-7/8"	2-3/4"	1-5/8"
038-FS442-WS	2-7/8"	2-3/4"	1-5/8"



## Ives Floor Door Stops & Manual Holder

- Manual type door holder ideal for interior or exterior use.
- Cast brass construction.
- Strike features hinged hook which engages the holder.
- Accommodates door undercut up to 2-1/2".
- Resilient rubber tip.
- Packed with wood screws.
- Meets ANSI/BHMA 156.16 L113761.
- MS - Packed with expansion shield and tamper  
WS - Packed with wood screws

Models	Overall Height	Overall Length	Base Width
038-FS451-WS	3-1/8"	2-3/4"	1-5/8"
038-FS451-MS	3-1/8"	2-3/4"	1-5/8"



## Ives Wall Holders

- Burnished cast aluminum.
- Non-marring rubber bumper.
- Packed with sheet metal screws.
- Finished US3, US27.
- Base diameter 1-5/8"
- Overall projection 3-3/4"

Model
038-WS65



## Ives Manual Wall Holders

- Heavy duty manual wall holders are constructed in cast brass.
- Base diameter: 2-3/8"
- Overall projection: 4"
- Strike height: 2"
- Strike width: 1"
- Finishes: US3, US4, US5, US10, US10B, US26 and US26D.
- Hinged strike furnished matches body material and finish.
- WS20X - Meets ANSI/BHMA 156.16 L1351  
WS20 - Meets ANSI/BHMA 156.16 L11341

Models	Description
038-WS20	Drywall Mounting
038-WS20X	Masonry Mounting

See price list for available finishes (finish chart is on the order form)



## Ives Plunger Type Door Holder

- Fed. Spec. 1154A, BHMA L11401, ANSI 156.16.
- Cast brass body, satin chrome finish.
- Plunger activates with minimal pressure.

Models	Description
038-FS1154	Plunger Type



FS18L



FS18S

## Ives Floor Stops

- Security door stops designed for use in high vandalism areas.
- Molded from flame resistant, resilient material around a heavy-duty stud.
- Ideal for jail or security cell areas
- FS18L also ideal for concrete wall applications

Models	Stop Height	Stop Diameter	Stud Length
038-FS18S	1-1/2"	2"	2-1/2"
038-FS18L	3-1/2"	2"	2-1/2"

## Ives Floor & Wall Stops/Holders

	Models	Description
	038-FB13	Dome Stop
	038-R14	Dome Stop Riser
	038-WS40	Automatic Wall Type Holder
	038-WS45	Adjustable Automatic Wall Type Holders
	038-WS45X	Adjustable Automatic Wall Type Holders, For Masonary Type Mounting
	038-FS17	Dome Stop
	038-FS1153M	Plunger Type Holder
	038-WS20	Manual Wall Type Holder
	038-WS20X	Manual Wall Type Holder
	038-SR64	Door Silencer 1/2" x 1/8"

See price list for available finishes (finish chart is on the order form)

## Ives Door Stops

### Wall Door Stop

- Cast anodized aluminum.
- Convex rubber, 2-1/2" diameter, 15/16" projection.
- Secured with set screw.



022-401

<b>Model</b>
<b>038-401 PA28</b>

### Wall Door Stop

- 2-7/16" diameter, 15/16" projection.
- Anodized aluminum, convex rubber.
- Secured by turning & locking.



022-406

<b>Model</b>
<b>038-406PA28</b>

### Floor Door Stop

- For doors without threshold.
- Gray, non-marring rubber bumper.



022-436

<b>Model</b>
<b>038-436PA28</b>

### Wall Mount Door Stop

- 3-5/8" projection, 2-1/4" diameter.
- Anodized aluminum.
- Resilient non-marring rubber tip.



022-447

<b>Model</b>
<b>038-447PA28</b>

### Floor Mount Door Stop

- 3" projection, 2-1/2" diameter.
- Anodized aluminum.
- Resilient non-marring rubber tip.



022-448

<b>Model</b>
<b>038-448PA28</b>

## Ives Plunger Type Door Holders




038-FS1153

038-FS1154

Models	Height	Width	Depth
<b>038-FS1153</b>	6-1/4"	1-1/2"	1-7/16"
<b>038-FS1154</b>	5-1/2"	2"	1-1/4"

## Ives Floor Stops

- Burnished wrought steel
- Soft, resilient gray rubber
- For undercut doors up to 1-1/2"
- Packed with screws & plastic anchors
- Finishes: US2C, US10
- Overall height 2-5/8"
- Base size 1-1/2" W x 2-3/4" L



<b>Model</b>
<b>038-FS434</b>



## Ives Wall Stops

- Hexagon section on both units aids in fastening unit when expansion shield is used. Rubber bumper features offset shoulder and threaded shank that screws into body of unit.
- Meets ANSI/BHMA 156.16 L113761
- Base diameter: 2"
- Overall projection: 3-3/4"

Models	Description
<b>038-WS11</b>	Drywall Mounting
<b>038-WS11X</b>	Masonry Mounting

See price list for available finishes (finish chart is on the order form)

## Ives Door Holders



### 455 Swing Down Door Holder

- 4" arm length - anodized aluminum
- Resilient non-marring rubber tip.
- Plate Height 1-3/4"
- Plate Width 1-3/4"
- ANSI/BHMA 156.16

Models	Description
038-FS455	Door to Floor Clearance 2" or less

\*Packed with expansion shield and lead shield.

## Ives Door Holders



### 452 Door Holder

- 5" arm length - anodized aluminum.
- Resilient non-marring rubber tip.
- Plate Height 2-1/8"
- Plate Width 1"
- ANSI / BHMA 156.16

Model	Description
038-FS452-4	Door to Floor Clearance 2" or less
038-FS452-5	Door to Floor Clearance up to 3"

## Rockwood Wall Bumpers

- Wrought Brass, Bronze, and Stainless Steel with DuraFlex Bumper
- Concealed mounting, convex bumper. Back plate prevents damage to wall.



057-406



057-409

Models
057-406 US3
057-406 26D
057-409 3
057-409 10B
057-409 26D

## Rockwood Floor Door Stops



057-471



057-440



057-477



057-442

Models
057-440 3
057-440 10
057-440 26D
057-442 3
057-442 26
057-471 26D
057-477 26D